

# MetaScape Opal Haze

Premium Etch Glass Effect Films



## Product Description

For faster, trouble-free application of glass manifestation, MetaScape Opal Haze offers ease of application by providing air with an exit route from under the graphic. MetaScape Opal Haze has been specifically formulated to provide a whiter, brighter, acid etched glass effect without any hint of sparkle. Suitable for many glass decoration applications, it is easy to cut and weed. The 80 micron film and high quality release liner and adhesive provide fast cutting and easy weeding on all computerised sign making equipment. The vinyl is resistant to most mineral oils, fats and fuels, aliphatic solvents, mild acids, diesel, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.

## Typical Applications

- For computer-cut etched glass effect graphics, and window manifestation.

## Application Guidelines

- Dry application.
- Not suitable for use on Polycarbonate. Application between two sheets of glass is not recommended.
- Refer to [www.metamark.co.uk/technical](http://www.metamark.co.uk/technical) for further advice on application to glass.

## Face Film

Face Film:	Polymeric Calendered PVC
Gauge:	80 micron nominal
Tensile Strength	47N/25mm MD / 43N/25mm TD
Elongation at break	180% MD nominal
Shrinkage	-0.5% MD, -0.2% TD

## Adhesive

Type	'MetaScape' permanent clear solvent acrylic with air channels.
Weight	22gsm nominal
Adhesion to glass 20 mins	15N/25mm nominal
Adhesion to glass 24 hour	20N/25mm nominal
Perceived tack	Medium
Shear strength	Medium to High
Application temperature	+5°C to +60°C
Service temperature	-30°C to +110°C

## Light Transmission

Opal Haze	75%
-----------	-----

## Release Liner

Print Type	'MetaScape' print Structured layflat kraft paper with PE coating
Gauge	145mym nominal
Weight	140 gsm nominal

## Finishes

Finishes Available	M7A-OH MetaScape Opal Haze
--------------------	----------------------------

## Durability

Shelf Life	1 year
External weathering	7 years in vertical exposure under Northern European conditions
Fire Rating	Class B. Classification compliant with BS EN 13501-1:2007
Chemical Resistance	Resistant to mineral oils, fats and fuels, aliphatic solvents, mild acids, salt and alkali for e.g. diesel oil, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.

**Warranty:** Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

## Metamark (UK) Limited

○ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147

○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

[sales@metamark.co.uk](mailto:sales@metamark.co.uk)

[www.metamark.co.uk](http://www.metamark.co.uk)