

myMEDIA 5626 SparkleLam Anti-Slip

Product Description

myMEDIA 5626 SparkleLam Anti-Slip is a 200 µm thick, textured, robust PVC laminate with glitter particles that have a slightly metallic appearance. It has been specially developed for eye-catching floor advertising and is also used as an effect laminate for striking designs and graphics. The solvent-based adhesive provides good moisture resistance. The textured surface ensures good slip resistance indoors and complies with slip resistance R10 according to DIN 51130. The glittering surface clearly sets floor graphics apart from others and makes for a real eye-catcher. The visual properties are also ideal for POS, displays, roll-ups, pop-ups, luxury photos, wedding albums, etc. The stability of the material makes it very easy to process. If used properly, it can be expected to last up to 4 months indoors as floor advertising (depending on the stress).

Physical Characteristics

Front material	Monomeric plasticised PVC film with glitter effect		
Thickness / Weight	200 µm		
Colour / Finish	Transparent with glitter effect, textured		
Adhesive	Solvent-based acrylic adhesive, permanent		
Liner	One side PE-coated kraft paper, 120 g/m ²		
Durability	Up to 2 years indoor, up to 1 year outdoor (vertical exposure)		
Service life floor graphics	Up to 4 months as indoor floor laminate (depending on use)		
Application temperature	>= +10°C		
Temperature range	-10°C to +70°C		
Adhesion after 24h	16 N/25 mm		FINAT FTM 1
Dimensional stability	<1,5 mm shrinkage		FINAT FTM 14
Slip resistance	R10		DIN 51130
Tensile strength	> 21 MPa (machine)	> 20 MPa (cross)	DIN EN ISO 527
Elongation	> 275 % (machine)	> 290 % (cross)	DIN EN ISO 527
Fire behaviour	Self-extinguishing		DIN 75200

Storage

Shelf life	Up to 1 year in unopened original packaging
Storage conditions	+18°C to +25°C at 50% relative humidity
Storage notice	Remove the roll from the laminator after each use and store in the original sealed packaging.

Printing Method

Compatible inks	Not recommended
-----------------	-----------------

Processing and converting

Lamination	Cold
Laminating temperature	+15°C to +35°C
Laminating speed	0 to 2 m/min.

myMEDIA 5626 SparkleLam Anti-Slip

Advantages and features

- Unique effect laminate
- Exclusive glitter effect
- Very robust material with 200 µm thickness
- Suitable for floor advertising and finishing
- Slip resistance R10 according to DIN 51130
- Up to 2 years durability in vertical outdoor applications
- Up to 4 months as floor advertising indoors
- Good moisture resistance
- High abrasion resistance
- Good adhesion to UV inks
- Reduced dirt acceptance
- Very good laminating properties and workability
- Excellent price/performance ratio

Applications

- Eye-catching designs and graphics
- Exclusive interior floor graphics
- Finishing of images
- Finishing of displays, roll-ups, pop-ups
- High-quality shop designs
- POS
- Presentations
- Eye-catcher promotions
- Interior design
- Trade fairs
- Events
- Lamination of UV prints

Important Notice

Information on physical and chemical characteristics is based upon tests, practical knowledge and experience. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Because of the variety of uses and applications, the purchasers should independently determine, prior to use, the suitability of this material to their specific use and carefully consider the suitability and performance of the product. The purchaser shall assume all risks for any use and application of the material. All specifications and technical data are subject to change without prior notice, errors and omissions expected. All warranty matters are regulated by our general terms and conditions.